| CHIP APPEARANCE | CHIP SIZE | | 1,6 × 2,0 mm | |
|--|-----------------------|---|--------------|---|
| The state of the s | CHIP THICKNESS | | | $460 \pm 30 \mu m \text{ (or } 280 \pm 30 \mu m)$ |
| 3 | DONDING DAD | 1 | INPUT | 240 × 240 μm |
| | BONDING PAD DIMENSION | 2 | OUTPUT | 240 × 240 μm |
| | | 3 | OUTPUT | 240 × 240 μm |
| | | 4 | ADJ | 240 × 240 μm |
| | SCRIBE LINE WIDTH | | | 80 μm |
| | TOP METAL | | | AlSi |
| | BACK METAL | | | – (or Ti-Ni(V)-Ag) |
| | WAFER SIZE | | | 100 mm |
| | | | | |
| | | | | |
| | | | | |

ABSOLUTE MAXIMUM RATINGS OVER OPERATING TEMPERATURE RANGE (UNLESS OTHERWISE NOTED)

| (| | |
|---|------------|------|
| | LM317 | UNIT |
| Input-to-output differential voltage, V _I - Vo | 40 | V |
| Continuous total dissipation at 25 °C free-air temperature | 2 | W |
| Continuous total dissipation at (or below) 25 °C case temperature | 15 | W |
| Operating free-air, case, or virtual junction temperature range | 0 to 125 | °C |
| Storage temperature range | -65 to 150 | °C |
| Lead temperature 1.6 mm (1/16 inch) from case for 10 seconds | 260 | *C |

RECOMMENDED OPERATING CONDITIONS

| | LM | 317 | UNIT |
|--|-----|------|------|
| | MIN | MAX | |
| Output current, I ₀ | 10 | 1500 | mA |
| Operating virtual junction temperature, T _J | 0 | 125 | °C |

electrical characteristics over recommended ranges of operating virtual junction temperature (unless otherwise noted) (see Note 1)


| PARAMETER | TEST CONI | LM317 | | | UNIT | |
|---|---|---|------|-------|------|-------|
| | | | MIN | TYP | MAX | |
| Input regulation (See Note 2) | V _I -V ₀ =3 V to 40 V, | =3 V to 40 V, TJ = MIN to MAX | | 0.01 | 0.04 | %/ V |
| | (See Note 3) | I ₀ = 10 mA to 1.5 A | | 0.02 | 0.07 | |
| Ripple rejection | Vo=10 V, f=120 Hz | | 65 | | dB | |
| | Vo=10 V, f=120 Hz 10-μF capacitor between | Vo=10 V, f=120 Hz 10-μF capacitor between ADJ and ground | | 80 | | |
| Output regulation | lo = 10 mA to 1.5 A, | Vo ≤5 V | | 5 | 25 | mV |
| | T _J = 25 °C, (See Note 3) | Vo > 5 V | | 0.1 | 0.5 | % |
| | lu - 10 mA lu 1.5 A, | V0 ≤ 5 V | | 20 | 70 | ····V |
| | (See Note 3) | Vo > 5 V | | 0.3 | 1.5 | % |
| Output voltage change with temperature | T _J = MIN to MAX | | | 1 | | % |
| Output voltage long-term drift (see Note 4) | After 1000 h at T _J = MAX and V _I -Vo =40 V | | | 0.3 | 1 | % |
| Output noise voltage | f= 10 Hz to 10 kHz, T _J =25°C | | | 0.003 | | % |
| Minimum output current to maintain regulation | V _I -Vo = 40 V | | | 3.5 | 10 | mA |
| Peak output current | V _I -Vo ≤ 15 V | 1.5 | 2.2 | | Α | |
| | V _I -Vo ≤ 40 V, T _J =25°C | | 0.15 | 0.4 | | |
| Adjustment-terminal current | | | | 50 | 100 | μА |
| Change in adjustment-terminal current | V _I -Vo=2.5 V to 40 V, lo = 10 mA to 1.5 A | | | 0.2 | 5.0 | μA |
| Reference voltage (output to ADJ) | V_I -Vo = 3 V to 40 V, Io=10 mA to 1.5 A, $P \le 15W$ | | | 1.25 | 1.3 | > |

Unless otherwise noted, these specifications apply for the following test conditions: V_I - V₀ = 5V and I₀ = 0.5 A. For conditions shown as MIN or MAX, use the appropriate value specified under recommended operating conditions.

NOTES:

- 1. All characteristics are measured with a 0.1 μF capacitor across the input and a 1 μF capacitor across the output.
- Input regulation is expressed here as the percentage change in output voltage per 1 V change at the input.
- Pulse testing techniques are used to maintain the junction temperature as close to the ambient temperature as possible.
- Thermal effects must be taken into account separately.
 Since long-term drift cannot be measured on the individual devices prior to shipment, this specification is not intended





NOTES:

A. Use of an input bypass capacitor is recommended if regulator is far from filter capacitors.

B. Use of an output capacitor improves transient response but is optional

C. Output voltage is calculated from the equation : $V_0 = V_{nef} \bigg(1 + \frac{R_2}{R_1} \bigg)$

 $V_{\rm ref}$ equals the difference between the output and adjustment terminal voltages

| | | Limit | | Condition | | | |
|----------------------------|--|--------|-------|-----------|--|------------|---|
| Nº | Name (Mode) | MIN | MAX | UNIT | INPUT | GROUN D | OUTPUT |
| 1 | Input current | - 85.0 | - | uA | 22 V | | -10 uA |
| 2 3 4 5 6 7 | Reference voltage (output to ADJ) | 1,225 | 1,275 | V | 45 V 45 V 42 V 42 V 4 V 4 V 30 V | 0 V | - 9 mA -50 mA - 50 mA - 9 mA - 9 mA - 200 mA - 200 mA |